



## Applications

- Mid-Water Navigation Tasks
- General Observation & Situational Awareness
- Manipulator & Tooling Tasks

# Goblin Shark IP




## Goblin IP Shark Camera

Goblin Shark IP – Wide Angle  
High Quality ultra-compact overview camera.

- 142 Deg Aov
- Fixed Lens
- 6000msw  
Depth Rating

For further information, email  
[camera.sales.uk@imenco.com](mailto:camera.sales.uk@imenco.com)





## Applications

- Mid-Water Navigation Tasks
- General Observation & Situational Awareness
- Manipulator & Tooling Tasks

## Goblin IP Camera

### Technical Specifications

Performance	
Video Resolution/format	1080p@30fps
Video Format	H.264 - RTP / RTSP / UDP
Latency (Glass to Glass)	170ms
Electrical	
Power Input	24 VDC/5w (10VDC - 36VDC)
Optical	
Lens	Fixed
AOV in water	3.6 Lens- 100° dia / 92° hor 2.9 Lens- 113° dia / 106° hor 1.8 Lens- 142° dia / 137° hor
Front Port	Dome BK7
Mechanical	
Dimensions	Diameter: 74mm main Body (79mm Front End) Length 123mm (excl. connector)
Weight	In air: 1.3 Kg In water: 0.4 Kg
Housing Material	Titanium
Standard Connector	DBH13 / 5506/1508
Environmental	
Operating Depth	6000 msw
Temperature	Operating: -5 to 40°C Storage: -20 to 60°C
Shock	30G peak acceleration, 25ms half sine duration, on all three axes
Vibration	10G, from 20 to 150HZ on all three axes
Electromagnetic Compatibility	BS EN 61000-6-3: 2007 Emission and BS EN 61000-6-1: 2007 Immunity

