

# OE13-126/127

## Applications

- Low Light Surveillance
- Mid-Water Navigation Tasks
- General Observation & Situational Awareness



## Extreme Low Light Monochrome Underwater CCD Camera

- 86° Wide AOV Excellent
- Low Light Performance
- 4500msw Depth Rating

The OE13-126 (CCIR) and OE13-127 (EIA RS170A) extreme low light, monochrome cameras have been designed primarily for use in subsea environments and are ideally suited to low light surveillance including mid-water and long-range navigation tasks, general observation and situational awareness applications.

The OE13-126/127 cameras offer both exceptional low light sensitivity and a wide AOV (86° diagonal) in water. The OE13-126/127 incorporates a back-illuminated and thinned (BIT) CCD sensor and advanced imaging processing technology, delivering a significantly improved low light performance over conventional low light SIT, CCD and CMOS sensors in all subsea environments.

The video image will appear in focus from 300mm in front of the port to infinity; making the OE13-126/127 an excellent choice for both navigation and general observation applications.

Packaged within a robust 4500msw depth rated titanium alloy housing the OE13-126/127 provides a standard definition composite video signal output via the Burton 5506-1508 connector or customer specified external connector.

The OE13-126/127 is supplied in a rugged transit case with a handheld infra-red remote control which has been intuitively designed for ease of use.

For further information, email  
[camera.sales.uk@imenco.com](mailto:camera.sales.uk@imenco.com)



## Applications

- Low Light Surveillance
- Mid-Water Navigation Tasks
- General Observation & Situational Awareness

# OE13-126/127

## Technical Specifications

<b>Performance</b>	
Horizontal Resolution	576 TVL/PH
Light Sensitivity	300 TVL video at $20 \times 10^{-6}$ lux faceplate
Minimum Scene Illumination	$350 \times 10^{-6}$ lux
Signal to Noise Ratio	70dB (weighted)
<b>Electrical</b>	
Scan Standards	625 lines 50 Hz CCIR (OE13-126) 525 lines 60 HZ EIA RS170A (OE13-127)
Video Output	1V pk-pk composite video into $75\Omega$
Power Input	16 – 24 VDC, 1.5A (max)
<b>Optical</b>	
Lens	4.8mm, F/1.8
AOV in water	Horizontal: 74° Vertical: 58° Diagonal: 86°
Iris Control	Automatic
Focus Range	300mm to infinity, fixed (in water)
<b>Mechanical</b>	
Dimensions	Diameter: 110mm (main body) Length: 209mm (excl. connector)
Weight	In air: 4.5 Kg In water: 2.5 Kg
Housing Material	Titanium alloy 6AL/4V ASTM B3 48
Connector	8 pin Burton 5506-1508 or customer specified
<b>Environmental</b>	
Operating Depth	4500 msw (other depth rated housing options available)
Temperature	Operating: -5 to 40°C Storage: -20 to 60°C
Shock	30G peak acceleration, 25ms half sine duration, on all three axes
Vibration	10G, from 20 to 150HZ on all three axes
Electromagnetic Compatibility	BS EN 61000-6-3: 2001 Emission BS EN 61000-6-1: 2001 Immunity

