



# Blacktip II HD-SDI

## Applications

- Inspection
- Restricted spaces
- Tooling



## Compact Zoom Subsea HD Camera


The Blacktip II Shark Colour Zoom HD Camera incorporates a 4Mpx - 1/3" CMOS sensor and features a 10x optical zoom lens.

With it's ultra-compact and lightweight Titanium body rated to 4000msw, it is an ideal camera for inspection of restricted spaces and for use in tooling applications.

- 49° AOV
- 10:1 Zoom Lens
- 4000msw  
Depth Rating

For further information, email  
[camera.sales.uk@imenco.com](mailto:camera.sales.uk@imenco.com)





## Applications

- Inspection
- Restricted spaces
- Tooling

# Blacktip II HD-SDI Shark Camera

## Technical Specifications

Performance	
Image Resolution	1080P@60fps
Minimum Scene Illumination	0.5Lux
Electrical	
Camera control	RS232/485, Bi-Polar, Tristate
Video Format	3G HD-SDI
Power Input	24 VDC, (12-36) 5w (max)
Optical	
Zoom	10 x optical (+16 Digital) F1.8 to 3.4
AOV in water	Diagonal: 49° Horizontal: 43°
Front Port	Sapphire Glass
Minimum Working Distance	10mm in water @zoom x1
Mechanical	
Dimensions	Diameter: 58mm Length: 143mm (excl. connector)
Weight	In air: 0.8 Kg In water: 0.5 Kg
Housing Material	Titanium
Connector	Seacon 5506-1508, CS-MSAJ-9-BCR or customer specified
Environmental	
Operating Depth	4000 msw
Temperature	Operating: -5 to 40°C Storage: -20 to 60°C
Shock	30G peak acceleration, 25ms half sine duration, on all three axes
Vibration	10G, from 20 to 150HZ on all three axes
Electromagnetic Compatibility	BS EN 61000-6-3: 2001 Emission BS EN 61000-6-1: 2001 Immunity

