



Whitetip II IP HD

Applications

- Inspection
- Resricted spaces
- Tooling




Compact Zoom Subsea Camera with Lights

The Whitetip Shark II Colour Zoom HD-SDI Camera incorporates a 4Mpx - 1/3" CMOS sensor and features a 10x optical zoom lens. With built-in LED lights and ultra compact and lightweight Titanium body rated to 4000msw; it is an ideal camera for inspection of restricted spaces and for use

- 49° AOV
- 10:1 Zoom Lens
- 4000msw Depth Rating

For further information, email
camera.sales.uk@imenco.com





Applications

- Inspection
- Restricted spaces
- Tooling

Whitetip II IP HD Shark

Technical Specifications

Performance	
Image Resolution	1080P@60fps
Minimum Scene Illumination	0.5Lux
light output	600 Lumens
Electrical	
Camera control	RS232/485, Bi-Polar, Tristate
Video Format	3G HD-SDI
Power Input	24 VDC, (12-36) 12W (max)
Optical	
Zoom	10 x optical (+16 Digital) F1.8 to 3.4
AOV in water	Diagonal: 49° Horizontal:43°
Front Port	Sapphire Glass (Camera) /Acrylic (lights)
Focus Range	10mm to Infinity in water
Mechanical	
Dimensions	Diameter: 58mm Length: 143mm (excl. connector)
Weight	In air:.0.8 Kg In water: 0.5 Kg: Packaged weight 1.6 kg Packaged Dimensions 296mm x 212mm x 96mm
Housing Material	Titanium
Connector	DBH2013 or customer specified
Environmental	
Operating Depth	4000 msw
Temperature	Operating: 0 to 40°C Storage: -20 to 60°C
Shock	30G peak acceleration, 25ms half sine duration, on all three axes
Vibration	10G, from 20 to 150HZ on all three axes
Electromagnetic Compatibility	BS EN 61000-6-3: 2001 Emission BS EN 61000-6-1: 2001 Immunity

